

MKW-V/MKW-H

Waterproof Standalone A&C Device
Supporting Card & Password
Authentication



MKW-V and MKW-H are waterproof standalone access control devices with an IP65 metal case and a keypad. The device supports verification with passwords and RFID cards.

MKW-V and MKW-H can either be used as readers connecting with a control panel or as A&C standalone devices.



Features

- Metal case
- IP65 - waterproof and dustproof
- Touch keypad
- A&C Standalone or Reader


Specifications

Model	MKW-V	MKW-H
Operating Frequency	125KHz / 13.56MHz	
RFID Type	EM Card / ISO 14440 Type A, S50 / S70 Mifare	
Protection Standard	IP65	
Operating Voltage	DC9 - 14V	
Operating Temperature	-20°C ~ 45°C (-4°F ~ 113°F)	
Humidity Storage	20% ~ 80%	
Dimensions (L*W*H)	160 * 50 * 20.5 (mm) (±3 mm)	120 * 86 * 20.5 (mm) (±3 mm)
A&C Standalone	User Capacity: 5,000	
	Password Capacity: 5,000	
	Password: 4 to 6 digits	
	Verification Modes: Card Only / Password Only / Card + Password	
	1 Relay / 1 Door Sensor / 1 Exit Button / 1 Doorbell / 1 Tamper Alarm	
Reader	Wiegand Reader W26/W34	

Configuration



Dimensions (mm)



Note:

The intense sunlight and heavy rain conditions will adversely impact the buttons. Covering the buttons under the fierce sunlight by hand is recommended. Wipe the keypad dry when there are raindrops on it.

