

ProID RS485 Series Reader



ProID20-RS



ProID30-RS

The ProID-RS family of card readers is designed to offer card technologies options to customers such as 125KHz EM, 13.56MHz IC, DESFire.

With a robust all-weather protection and a beautiful modern design, the ProID-RS family is the best choice for indoor or outdoor applications.

Features

- High stability and energy efficiency.
- LED light and touch keypad.
- RS485 output.
- Waterproof design suitable for indoor or outdoor applications.
- Black or white color available.

Specifications

Read Range

≥5cm

Reading Time

≤300ms

Input Port

External LED Control
External Buzzer Control

Material

ABS+PC

Supported Panel

InBio160 Pro, InBio260 Pro
InBio460 Pro

Output Format

RS485

Power

Operating Voltage 7~13V DC
Current Draw < 80mA

LED

Pulsing White Standby Light
Red and Green LEDs

Operating Temperature

-20 °C ~ 65 °C

Operating Humidity

10% ~ 90% Relative Humidity
Non-Condensing

Audio

Beep

Index Protection

IP65

Dimensions

ProID20/30-RS: 90 × 90 ×
16mm.

ProID RS-485 Reader List

ProID20 BE-RS	ProID20 BM-RS	ProID20 WE-RS	ProID20 WM-RS	ProID20 BD-RS
ProID20 WD-RS	ProID30 BE-RS	ProID30 BM-RS	ProID30 WE-RS	ProID30 WM-RS

How to Order ProID Series?

ProID20 WE - RS

